

AQUAPHOR®
water filters

NEW

Solo HF PRO

Under-sink system

Antibacterial protection



Technologies

High-tech water treatment solution



AQUALEN™

Unique ion-exchange fiber.
Fully eliminates heavy metals and
permanently absorbs harmful impurities.



CARBON BLOCK + AQUALEN™

It is a technology of manufacturing filtering
media of different degree of porosity
for any level of water contamination.
CB significantly increases the service life
of replaceable AQUAPHOR cartridges without
compromising the quality of purification.



Hollow fiber technology

Provides highly effective antibacterial barrier
against impurities up to 0.1 microns.



AUTO LOCK

Instant replacement of cartridges.
Clean and safe maintenance.



STC (Absolute safety)

Materials used in AQUAPHOR water filters
meet “Food Grade” global safety standards.

AQUAPHOR®


Removes:

- **Bacteria**
- Active chlorine
- Heavy metals
- Organic compounds
- Pesticides
- Nitrates, nitrites
- Arsenic

Resource – 3000 L



AUTO LOCK
Easy replacement
of cartridges



**FAUCET NOT
INCLUDED**



Recommended filtration rate (performance) – 1.5 l/min
Diameter x Height: 90 x 341 mm

Logistics

Under-sink system Solo HF PRO



Packaging Unit	Length, mm	Width, mm	Height, mm	Gross weight, kg	No of pieces per shipping carton	Barcode	Article
Unit packing	119	109	400	1,129	1	4744131012414	525535
Shipping carton	366	226	415	6,840	6	14744131012411	
</							

Logistics

Replacement filter cartridge Pro HF



Packaging Unit	Length, mm	Width, mm	Height, mm	Gross weight, kg	No of pieces per shipping carton	Barcode	Article
Unit packing	85	85	329	0,65	1	4744131016443	511371
Shipping carton	361	266	347	8,152	12	14744131016440	

	Quantity per pallet, pcs	Quantity per layer, pcs	Quantity of Outer cartons per pallet, pcs	Quantity of layers per layer, pcs	Pallet height, mm
EU-pallet	540	9	45	5	1879
FIN-pallet	660	11	55	5	1880

AQUAPHOR®
water filters

aquaphor.com