

Declaration of performance: No. STES2004.13813.1

1. Unique identification code of the product-type: **UNIPLAN ECO**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

CEMENTITIOUS SELF-LEVELLING COMPOUND FOR SUBSTRATES (CT-C30-F7)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Cementitious screed material for internal use in floor construction


4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI AS – Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4
System 3 for reaction to fire
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The notified testing laboratory MPA Dresden GmbH N. 0767, performed the determination of the class of reaction to fire on samples taken by the manufacturer, under system 3, and issued the report N. 2012-B-0952/01.
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire Release of corrosive substances: Water permeability: Water vapour permeability: Compressive strength: Flexural strength: Wear resistance: Sound insulation: Sound absorption: Thermal resistance: Chemical resistance:	Class A2 _{fi} -s1 CT NPD NPD C30 F7 NPD NPD NPD NPD NPD	EN 13813:2002



10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**
(name and function)

Sagstua, 01/07/2013
(place and date of issue)


(signature)

CE MARKING according to CPR 305/2011 and EN 13813:2002

 0767	 MAPEI Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no																						
<p>13</p> <p>STES2004.13813.1</p> <p>EN 13813:2002 CT-C30-F7</p> <p>UNIPLAN ECO</p> <p><i>Cementitious screed material for internal use in floor construction</i></p> <table><tr><td>Reaction to fire:</td><td>Class A2_{fl}-s1</td></tr><tr><td>Release of corrosive substances:</td><td>CT</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Water vapour permeability:</td><td>NPD</td></tr><tr><td>Compressive strength:</td><td>C30</td></tr><tr><td>Flexural strength:</td><td>F7</td></tr><tr><td>Wear resistance:</td><td>NPD</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr></table>		Reaction to fire:	Class A2 _{fl} -s1	Release of corrosive substances:	CT	Water permeability:	NPD	Water vapour permeability:	NPD	Compressive strength:	C30	Flexural strength:	F7	Wear resistance:	NPD	Sound insulation:	NPD	Sound absorption:	NPD	Thermal resistance:	NPD	Chemical resistance:	NPD
Reaction to fire:	Class A2 _{fl} -s1																						
Release of corrosive substances:	CT																						
Water permeability:	NPD																						
Water vapour permeability:	NPD																						
Compressive strength:	C30																						
Flexural strength:	F7																						
Wear resistance:	NPD																						
Sound insulation:	NPD																						
Sound absorption:	NPD																						
Thermal resistance:	NPD																						
Chemical resistance:	NPD																						