

Declaration of performance: No. CPR-IT1/0356

1. Unique identification code of the product-type: **ULTRAMASTIC III**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

IMPROVED DISPERSION ADHESIVE FOR CERAMIC TILES

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Internal and external tiling on walls, internal tiling on floors**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI S.p.A. – Via Cafiero, 22 – Milano (Italy) www.mapei.it**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified testing laboratory TUM München, No. 1211, performed the determination of the product-type on the basis of type testing on samples taken by the manufacturer, under system 3, and issued the test report No. 25040266/Gi.

The notified testing laboratory MPA Dresden, N. 0767, performed the determination of the reaction to fire on samples taken by the manufacturer, under system 3, and issued the classification reports No. 2009-B-4835/06 and . No. 2009-B-4835/09.

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance


Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class B _{fl} -s1 B-s1,d0	EN 12004:2007 + A1:2012
Bond strength as: - initial shear adhesion strength	≥ 1,0 N/mm²	
Durability for: - shear adhesion strength after heat ageing - shear adhesion at elevated temperatures - shear adhesion after water immersion	≥ 1,0 N/mm² ≥ 1,0 N/mm² ≥ 0,5 N/mm²	
Release of dangerous substances	See SDS	

- 10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**
(name and function)

Milan, 01/07/2013
(place and date of issue)



 (signature)

CE MARKING according to CPR 305/2011 and EN12004:2007+A1:2012

 1211 0767	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
<p style="text-align: center;"> 04 CPR-IT1/0356 EN 12004:2007+A1:2012 ULTRAMASTIC III Improved dispersion adhesive for internal and external tiling on walls and internal tiling on floors </p>	
Reaction to fire Bond strength, as: Initial shear adhesion strength Durability for: Shear adhesion strength after heat ageing Shear adhesion at elevated temperatures Shear adhesion after water immersion Release of dangerous substances	Class B _{fl} -s1/B-s1,d0 $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ see SDS