


# Sakkelit



## Sakkeli, leimattu


Pintakäsittelynä kuumasinkitys  
varmuuskerroin  $\delta:1$

CE-merkityjä. Ei saa lämpökäsitellä.

Sakkeleihin on merkitty max. työkuorma ja nimellismitta.

CE  
EN 13889

Koko"/d1 mm	b1	b3	d3	h1	Työ kuorma	Tuote n:o
5/16	8	13	21	21	750 kg	0523 900 0516
3/8	10	16	26	26	1000 kg	0523 900 038
1/2	13	21	33	30	2000 kg	0523 900 012
5/8	16	27	43	42	3250 kg	0523 900 058
3/4	19	32	51	48	4750 kg	0523 900 034
7/8	22	36	58	57	6500 kg	0523 900 078
1	25	43	68	62	8500 kg	0523 900 01




## Sakkeli

Pintakäsittelynä sinkitys

Ei saa käyttää nostovälineissä



Koko"/mm	b1	h1	Kuormitus	Sinkitty	Haponkestävä
3/16	5	10	80 kg	0523 903 16	0526 009 85
1/4	6	12	100 kg	0523 901 4	0526 009 86
5/16	8	16	200 kg	0523 905 16	0526 009 88
3/8	10	20	300 kg	0523 900 38	0526 009 810
1/2	12	24	500 kg	0523 900 12	0526 009 812
5/8	16	32	800 kg	0523 900 58	0526 009 816
3/4	19	38	1100 kg	0523 900 34	
7/8	22	44	1500 kg	0523 900 78	
1	24	48	2000 kg	0523 900 1	



## Palomiehenhaka

DIN 5299C

Erilaisiin kiinityksiin ja ripustuksiin

Pintakäsittelynä sinkitys




L x d1	d2	f	m	Kuormitus	Sinkitty	Haponkestävä
60 x 6	9	5	8	120 kg	0524 60 6	0524 060 61
80 x 8	10	8	9	230 kg	0524 80 8	0524 080 81
90 x 9	12	9	10	250 kg	0524 90 9	
100 x 10	15	10	11	350 kg	0524 100 10	0524 010 011
120 x 11	18	11	16	450 kg	0524 120 11	0524 012 020

## Simplex-jousihaka

DIN 5287B

Sinkitty

L mm	d2 mm	m mm	Tuote n:o
40	9	5,5	0524 900 40
50	10	6,5	0524 900 50
60	12	7,5	0524 900 60
80	18	10	0524 900 80



## Vanttiruuvi

Valuterästä, pintakäsittelynä sinkitys

Koukku/silmukkapäättein

Ø mm	L1	L3	b1	L4	d1	Tuote n:o
5	50	40	7,5	44	8	0521 955 0
6	110	85	8,5	80	9	0521 961 00
8	110	85	11	84	10	0521 981 25
10	125	112	13,5	105	14	0521 910 125
12	125	117	15,5	115	16	0521 912 125